



TRUCK BODIES

— EXPECT THE BEST —

NEW

DB3000

**PICKUP
DUMP BODIES**



SHOWN EQUIPPED WITH

- 8'8" SRW Pickup Dump Body
- Electric Telescopic Hoist
- ICC Bar
- 2" Hitch Receiver
- Backup Alarm
- Trailer Connector
- Aluminum Tailgate
- Manual Tarp Kit with Pull Bar

**For Box Delete
Pickup Trucks**

A&K **EQUIPMENT CO.**
INCORPORATED

732-388-5333
www.akequipment.net

NEW

Pickup Dump Bodies Standard Specifications & Options



Aluminum Tailgate Specs

- Constructed with $\frac{3}{16}$ ALUMINUM
- Fully boxed frame with 2 vertical braces
- Standard height 6" higher than sides
- Double acting with bottom release pin at rear both sides, upper release is quick-release screw pin style
- Standard with spreader chains and banjo eye chain holders on rear posts

Standard Features and Specifications

- Standard dump body includes 41" bulkhead & led light kit
- Light kit consist of S/T/T & reverse lights 1-per side, marker & clearance lights with rubber grommets & wiring harness
- 5'X 6.7 Lb. Structural channel long sills
- 3" Formed channel 12 ga. Crossmembers on 12 O.C.
- 12 ga. steel floor formed with inner side wall
- 12 ga. outer wall sides with box formed top and v-formed outside wall
- Front and rear posts 6" higher than sides with side boards brackets
- Available in 12" & 16" sides
- SRW standard width 81" outside and 71 $\frac{3}{4}$ " inside
- Drw standard width 96" outside and 86 $\frac{3}{4}$ " inside
- Painted black with primer undercoat & urethane top coat (other colors available)

Options

- 12" cab shield
- Fold down sides
- No tarp kit

Hoist & Subframe Standard Specifications

- 100" long angle subframe designed for 2019 & newer Ford Box Delete 56" CA chassis
- Body long sills sit down in angle subframe for a lower overall mounting height
- Mounting brackets and hardware included
- Front mount telescopic cylinder with 78" stroke for a 47 degree dump angle
- 5 ton hoist and subframe
- Single acting 12 volt power unit installed in between subframe angles and body long sills
- Can be installed on basically any 56" CA Box Delete chassis with slight modifications to subframe & mounting brackets

Standard Length and Approximate Body Weight/Cubic Yards capacity*

Length	Width for	Side Height	Approx. Wt.	**Payload Cap.	Capacity
8'8"	SRW	12"	1610	(1) 1.3 tons	1.9 cu. ya
8'8"	DRW	12"	1710	(2) 2.5 tons	2.3 cu. yd
8'8"	SRW	16"	1630	(1) 1.3 tons	2.5 cu. yd
8'8"	DRW	16"	1740	(2) 2.5 tons	3.1 cu. yd.

[1] Payload capacity is approx. and based on Ford's F350 SRW box delete truck with diesel, 4x4 and reg. cab with a 11,000 lb. GVW

[2] Payload capacity is approx. and based on Ford's F350 DRW box delete truck with diesel, 4x4 and reg. cab with a 14,000 lb. GVW

** Payload capacity represents maximum allowable weight of people & cargo and is reduced by optional equipment weight.

True payload must be determined after complete upfitted truck is weighed.

- Final truck installation requirements may be chassis OEM box delete wire harness kit, backup camera kit, etc.
- Truck may also need to be reprogrammed by a dealer to accept it as a box delete finished truck
- This should not be any different than any other box delete install such as a service body



TRUCK BODIES
— EXPECT THE BEST —

www.shtruckbodies.com

6 1 0 . 2 7 3 . 0 1 5 7

Screw Pin Top Release