



Model AF2000 Specifications

• Unit has an overall height of 49" and width of 82"

Model Number	Hopper Length	Struck	Capacity Rounded		12 Ext	Approx. lbs.	Truck C.A. in.
AF-2000-8	8	5.0	5.6	1.0	2.0	1810	60
AF-2000-9	9	5.5	6.3	1.1	2.3	1940	60-72
AF-2000-10	10	6.0	7.0	1.2	2.6	2040	72-84
AF-2000-11	11	6.5	7.2	1.3	2.9	2170	84
AF-2000-12	12	7.0	8.4	1.4	3.2	2320	102
AF-2000-13	13	7.5	9.1	1.5	3.5	2490	102
AF-2000-14	14	8.0	9.8	1.6	3.8	2620	102-112
AF-2000-15	15	8.5	10.5	1.7	4.1	2780	112-124
AF-2000-16	16	9.0	11.2	1.8	4.4	2890	124-136



304 Stainless Steel Hopper

Hopper

- Fully welded 10 gauge steel, heavy duty
- Front and rear panel 23° interior slope for ease of material flow
- Sides 45° slope, 10 gauge steel gussets
- Gussetts welded at bottom to a 3" tubing, to serve as skid runner for ease in mounting
- Rear feedgate 7 gauge door controlled by screwjack

Conveyor

- 7 gauge steel side channels
- 24" roller chain with 3/8"x1 1/12" bars
- Bolt in bed plate
- Gearbox 6:1 spur gear type
- Spring loaded chain take up

Material Chute

- Fully enclosed, 10 gauge steel construction
- · 4 external adjustable deflectors
- 2 internal baffles, adjustable without tools
- Vertically adjustable in 3" increments
- Can swing above bottom of conveyor for ground storage or bulk discharge
- · Diverter Chute for quick loading

Spinner

- Powered by a high-speed hydraulic motor
- 20" disc with 6 fins

Options

- 304 Stainless steel hopper
- Hopper Extensions
- Dump body or chassis mount
- Top Screens
- Fenders
- Chain oiler
- Inverted V
- · Cab Shield



Air-Flo Manufacturing 40 South Main Street Prattsburgh, NY 14873

phone: 607.522.3574 fax: 607.522.4412