

WALTCO. Proudly Made In the USA

EM/TC

FLIPAWAY GATE

2,500 lb. and 3,300 lb. Capacities

Easy to Operate, Maintain and Store Flipaway Gate Features Twin Cylinders for Maximum Clearance and Performance

Products shown may feature optional equipment. Content subject to change without notice.

STANDARD EM/TC SERIES ADVANTAGES INCLUDE:

New wider and deeper platform sizes

Steel Platforms:


- 40" x 84" + 4" ramp - 44" x 84" wedge - 46" x 84" + 4" ramp - 50" x 84" wedge

- Aluminum Platforms: – 44" x 84" wedge – 50" x 84" wedge
- Twin cylinders require less mounting clearance and store higher up underneath truck for maximum ground clearance
- Twin cylinder hitch design works on lower bed height than single cylinder design (47" for single and 39" for twin)
- Bed extension with reinforced angle along entire width makes installation easier and reduces dishing
- 36" to 56" bed height range (Note: Larger platform 46"+ 4" & 50" wedge fits 39" (laden) – 56" bed height only)
- Grease fittings and maintenance free bearings at all major hinge points
- Easier installation with preset "A" dimension. Pump and cylinder installed and tested at factory
- Roll pins replaced with bolts to allow easier maintenance
- Snubber kit reduces potential liftgate wear caused by vibration during travel
- Powder coat finish with zinc primer on key liftgate components produces a high-quality finish that is exceptionally resistant to corrosion and abrasion


OPTIONAL EQUIPMENT:

- Hand-Held Pendant Control allows driver to operate the truck from the ground or bed level
- Underride option available

EMW/TC-25, EMW/TC-33







GROUND LEVEL



EM/TC gate in stowed position



EM/TC

FLIPWAY GATE



Bolt-on parking bar shown above



Optional steel dock bumper with built-in traction step and full coverage rubber pad

SPECIFICATIONS

MODEL	CAPACITY	PLATFORM	RAMP
EM/TC-25	2,500 lbs.	40"x 84"	4"
EMW/TC-25	2,500 lbs.	44"x 84"	Wedge
EM/TC-25	2,500 lbs.	46"x 84"	4″
EMW/TC-25	2,500 lbs.	50"x 84"	Wedge
EM/TC-33	3,300 lbs.	40"x 84"	4″
EMW/TC-33	3,300 lbs.	44"x 84"	Wedge
EM/TC-33	3,300 lbs.	46"x 84"	4″
EMW/TC-33	3,300 lbs.	50"x 84"	Wedge
AP (Aluminum Platform)			
EMW/TC/AP-25	2,500 lbs.	44" x 84"	Wedge
EMW/TC/AP-25	2,500 lbs.	50" x 84″	Wedge
EMW/TC/AP-33	3,300 lbs.	44" x 84"	Wedge
EMW/TC/AP-33	3,300 lbs.	50" x 84"	Wedge

Note: "EMW" denotes full-dip wedge style platform models

The 46"+4" platform and the 50" wedge have a minimum bed height of 39" laden

OPTIONAL EQUIPMENT (CONTINUED):

- Remote Pump Mounting Kit offers the flexibility to install the pump unit independently from the liftgate mount assembly when mounting space is an issue (recommended for low-bed height mounting applications)
- Walk Ramp Installation Kit allows liftgate to be used in conjunction with slide out walk ramp (for bed heights 42"– 54" only)
- Power-Down Operation for consistent performance regardless of weather conditions or temperature (dual solenoid)
- Cab Shut-Off Switch allows operator to shut off power to control switches, preventing unauthorized use of the liftgate
- Dual Controls (street-side control) for added driver convenience
- Single or two-step dock bumpers with or without lights protect the liftgate from damage caused by backing into loading docks
- Receiver-style hitch (Class IV 10,000 lb. rating with 1,000 lb. tongue weight) adds trailer towing versatility to vehicles with E Series liftgates (Draw bar and ball hitch not included; 39" to 56" Bed Height with twin cylinder)
- Draw Bar Kit (Class III) gives 13" ball height range flexibility (Ball hitch not included)
- Optional dual cart stops (only available on wedge ramps)
- Customized Options contact factory

Products shown may feature optional equipment Content subject to change without notice.



Waltco Lift Corp. Corporate Office United States 285 Northeast Ave. Tallmadge, OH 44278 P: 330.633.9191 F: 330.633.1418 Waltco Lift Corp. United States 620 S Hambledon Ave. City of Industry, CA 91744 P: 626.964.0990 F: 626.964.0149 Waltco Lift Inc. Canada 90 North Queen St. Etobicoke, ON M8Z 2C5

Bed Ht: 36"- 56"