



SHOWN EQUIPPED WITH

- 14' Body with L-Pack Toolboxes
- PTO Hydraulic Hoist
- Ladder Roof Rack with Side Access Ladder
- Inside Ladder/Pruner Box
- ¾" Pintle Hitch Plate
- ICC Bar
- 8 Ton Pintle Combo Hitch
- · Backup Alarm

INSTALL OPTIONS:

- Dump Hoist Electric or PTO
- · Rear Hitch Plate or Hitch Receiver
- Underbody Toolboxes
- · Backup Alarms

- · Brake Controller
- Trailer Connectors
- ICC Bars





CB3000 CHIPPER/FORESTRY BODIES

Standard Specifications & Options

- Body includes 66" or 72" high sides including tapered roof top with vents in side wall
- 30" high rear barn doors with dual cam latch system
- LED light kit, includes; 6" oval S/T/T and reverse lights in rear apron and roof channel, %" rear and side marker and clearance lights, & wiring harness, meets (FMVSS108)
- Structural channel long sills; 7" x 9.8 lb. channel
- 3" 10 ga. formed channel crossmembers 12' O.C.
- 4" x 5.4 lb. channel rear rail
- 10 ga. smooth steel floor with formed side rails
- 10 ga. smooth steel sides with box tubing top rail
- 14 ga. formed steel roof with roof bows
- 95½" standard outside width with 89½" inside width
- Painted white with primer undercoat & urethane top coat (other colors available)
- Black interior rubberized chip protection coating, floor, sides 8 top

Cubic Yard Capacity		
Overall Outside Dimensions, length x width	Approx. weight	Cubic Yards
96" x 12' x 66" high	3161	17
96"'x 14' x 72" high	3492	22
96" × 16' × 72" high	3871	25



OTHER BODY OPTIONS

- Front cutout for B-pack toolbox overhang
- Ladder rack, bolt-on three-piece with ladder roller on curbside
- 17" x 69" ladder with two rung flip down section, bolt on for 66" high body
- 17" x 75" Ladder with two rung flip down section, bolt on for 72" high body
- Ladder storage compartment with shelf for pruners on curbside, with sloped top

